

CM – Instructions

These instructions apply to Alloc Wall&Water.

1. Area of use

Alloc Wall&Water is an interior wall panel to be installed on existing walls in domestic and public environments. Alloc Wall&Water is designed to be used in dry- and wet areas, like bathrooms, showers and other areas with excessive water exposure.

2. Care

To prolong the life of the Alloc Wall&Water, it is necessary to take precautions against unnecessary loads on the surface.

When separating the panels from its packaging, the panels are to be lifted off each other in order to prolong the surface finish.

3. Maintenance/ Cleaning

Dry cleaning methods are recommended.

For difficult cleaning, you are recommended to use a well wrung-out cloth with clean lukewarm water. Where detergents are used in the water, synthetic detergents should be used. Organic detergents leave behind a thin film of grease on the surface and will result in visible stains on the surface..

Dry methods

For daily cleaning, we recommend that you use a broom, vacuum cleaner or mop. Microfibre mops are ideal.

Wet methods

Stubborn stains can be wiped off with a well wrung-out damp cloth. Never use highly concentrated soap solutions on the floor. Very stubborn stains can be cleaned as shown in the table below:

Stains	Removed with
Grease, salt, wine, chocolate	Lukewarm soapy water (synthetic detergent)
Lipstick, oil, asphalt, shoe marks, soot, nail varnish	Acetone
Wax from candles	Wait until it is hard and scrape it off carefully
Chewing gum	Allow to cool, scrape off carefully, clean with acetone

If Alloc Wall&Water interior walls are subjected to spills from oil, crayons or enamel paint, these spills must be removed immediately. Otherwise there might appear slight color differences in the grooves of the panels.

The surface of Alloc Wall&Water interior walls is maintenance free. Cured silicone that comes from the joints in wet areas can easily be removed with a plastic scraper and cleaned with white spirit (paint thinner).

Removability

Alloc Universal can be removed and reinstalled.

The panels will also have a reuse value if you want to remove Alloc Universal.

Disposal must take place in accordance with the safety data sheet for Alloc Wall&Water.

4. Transport and Storage

Alloc Wall&Water is packed in perforated shrink wrap. This means that the packs may be stored and transported without temperature restrictions, but the packs must be protected from rain, snow and long-term bright light. The packages should be protected from shocks along the edges.

5. Health & environment

Alloc Wall&Water is tested according to national and European standards for emission and toxicity. Alloc Wall&Water is quality tested by a number of European test institutes and approved as interior wall panels in wet areas by NBI (Norwegian Building Institute, Oslo, Norway).

6. More information

For further information on Alloc Chateau or other products supplied by Alloc AS, please see Alloc brochure material or visit our web site: www.alloc.com

Please feel free to contact Alloc customer service by phone on +47 815 32 830 or by e-mail at alloc@alloc.no