

MATERIAL SAFETY DATASHEET (MSDS) ALLOC COMMERCIAL

1. PRODUCT AND COMPANY IDENTIFICATION

Common name: Alloc Commercial Laminate floor covering
Trade name: Alloc Commercial
Manufacturer: Alloc AS,
Fiboveien 26, NO-4580 Lyngdal
Telephone: + 47 3834 2213
Contact person: Tor Gunnar Bartnes

2. COMPOSITION AND INFORMATION ON INGREDIENTS

Name: Formaldehyde
CAS-nr. 50-00-0
% by weight < 0,01 %
Health -
Risk -

3. HAZARDS IDENTIFICATION

Installation of Alloc:
When cutting, make sure you operate on a steady support.

4. FIRST AID MEASURES

Installation of Alloc:
If bleeding should occur due to cutting, use bandage under compression to prevent further bleeding. If bleeding doesn't stop, seek medical attention.
If eye irritation occur due to repeated exposure of the eyes to dust from cutting, rinse immediately with plenty of water.
Cutting dust can be removed from skin by water and soap.

5. FIRE AND EXPLOSION DATA

Alloc Commercial is considered hardly inflammable.
Fire fighting media: Water, dry chemicals or foam.

6. ACCIDENTAL RELEASE MEASURES

Not applicable.

7. HANDLING AND STORAGE

Alloc is to be stored under roof, away from rain and snow.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Installation of Alloc:

When cutting with a motorised cutting tool or electrical saw, make sure to employ the recommended personal protection outfit/ equipment.

Safety glasses. Minimise skin contact to dust. Gloves suitable for protection against cuts from rough, sharp edges are recommended.

Wear dust protective mask when ventilation is inadequate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid material; HPL on HDF.
Colour:	Various colours/ patterns; otherwise not applicable
Odour:	Not applicable
Solubility description:	Insoluble in water and oil.
Density:	Approx. 965 kg/ m ³
PH-value, cons. solution:	Not available

10. STABILITY AND REACTIVITY

Alloc Commercial is considered stable and not reactive. It will not undergo any hazardous polymerisation.

11. TOXICOLOGICAL INFORMATION

Alloc Commercial is considered not dangerous for humans.

12. ECOLOGICAL INFORMATION

Not applicable.

13. DISPOSAL CONSIDERATIONS

Alloc Commercial can be left at ordinary disposal sites/ containers.

The strip of aluminium can be torn off and deposited in containers meant for recycling of metal.

The packing of plastic is made out of polyethylene (PE) and can be left at ordinary disposal sites/ containers.

The boxes of cardboard are to be deposited as ordinary paper where source segregation is a part of the local waste disposal programme.

The underlayment is made out of plastic and can be left at ordinary disposal sites/containers.

14. TRANSPORT INFORMATION

Road transport:	ADR	Not regulated
Ocean transport:	IMDG	Not regulated
Air transport:	IATA	Not regulated

15. OTHER REGULATORY INFORMATION

Not regulated

16. OTHER INFORMATION

Information sources:
Technical Datasheet

Definitions:

HPL High Pressure Laminate.
HDF High Density Fibreboard
MSDS Material Safety Datasheet
ADR Agreement on Dangerous Goods by road (Europe)
CAS Chemical Abstract Services
IATA International Air Travel Assosiation

MSDS is made of:

Technical Product Division
Alloc AS
Fiboveien 26
NO-4580 Lyngdal, Norway